



SPECIFICATIONS

PAGE: 1/2

LEAD – ACID RECHARGEABLE BATTERY

1. **Model:** RE12-12
2. **Nominal Capacity:** 12V 12AH (20HR)
3. **Mechanical Spec:**

(1) Measurements	Length	:	151±	1mm
	Width	:	98±	1mm
	Case Height	:	94±	1mm
	Overall height	:	97..5±	1mm

(2) Terminal : Faston tab 250

(3) Weight : Appox 4.2kg

(4) Case : Flame Retardant ABS

4. **Construction:**

This battery is composed of positive plates, negative plates, separators, container, lid, electrolyte etc, and is equipped with positive and negative polarity terminals.

Any emitted gas from the battery is minimized with the negative plate gas recombinant method, thus requiring no topping up of electrolyte.

5. **External appearance**

Battery shall be without acid leakage, conspicuous stain, scar or deformation.

6. **Performance**

6-1 Temperature of tested battery shall be 20-25°C, if not specified:

6-2 Discharge capacity:

Hourly rate	Discharge current	Final discharge voltage	Capacity
20 HR	600mA	10.50 V	12.00 Ah
10HR	1116mA	10.50 V	11.16 Ah
5HR	2040mA	10.20 V	10.20 Ah
1HR	7200mA	9.60 V	7.20 Ah

Battery capacity at time of delivery shall be 75% or more, provided it is tested within 14 days after delivery.

After delivery, the capacity shall exceed 95% of nominal within 3 charge / discharge cycles or 10 days float charge.



SPECIFICATIONS

PAGE: 2/2

6-3 Open circuit voltage:

12.6V (OCV) or more at $25 \pm 10^\circ\text{C}$.

6-4 Internal resistance:

$< 20\text{m } \Omega$.

6-5 Charging

Method	Given Voltage
Float Charge (trickle)	$13.65\text{V} \pm 0.15\text{V}$

6-6 Permissible temperature range

CONDITIONS	TEMPERATURE RANGE
Discharging	$-15^\circ\text{C} - 50^\circ\text{C}$
Charging	$0^\circ\text{C} - 40^\circ\text{C}$
Standing	$-15^\circ\text{C} - 40^\circ\text{C}$

6-7 Storage period without use

STORAGE TEMPERATURE	MAX. STORAGE PERIOD
20°C or less	9 months
$20 - 30^\circ\text{C}$	6 months
$30 - 40^\circ\text{C}$	3 months

6-8 Life expectancy (float standby applications @ 20°C) 7 years